IEEE HOME | SEARCH IEEE | SHOP | WEB ACCOUNT | CONTACT IEEE



Publications/Services Standards Conferences Careers/Jobs RELEASE 1.7

Welcome

United States Patent and Trademark Office



Help FAQ Terms IEEE Peer Review

Quick Links

Search Results [PDF FULL-TEXT 860 KB] PREV NEXT DOWNLOAD CITATION

Welcome to IEEE *Xplore*®

O- Home

O- What Can I Access?

C Log-out

Tables of Contents

O- Journais & Magazines

- Conference **Proceedings**

O- Standards

Search

O- By Author

O- Basic

) - Advanced

Member Services

O- Join IEEE

- Establish IEEE Web Account

O- Access the **IEEE Member Digital Library**

Print Format

Credit-based flow control for ATM networks

Kung, N.T. Morris, R.

Request Permissions

RIGHTS LINK(

Harvard Univ., Cambridge, MA, USA; This paper appears in: Network, IEEE

Publication Date: March-April 1995

On page(s): 40 - 48 Volume: 9, Issue: 2 ISSN: 0890-8044 Reference Cited: 14 CODEN: IENEET

Inspec Accession Number: 4931626

Abstract:

Simulation, analysis, and experiments on switching hardware have shown tha variety of traffic patterns, credit control is fair, uses links efficiently, minimize guarantees no cell loss due to congestion. The credit-based mechanism prog authors provides flow control tailored to ATM networks

Index Terms:

adaptive control asynchronous transfer mode protocols telecommunication congestic telecommunication network management ATM networks adaptive buffer allocation as loss congestion credit update protocol credit-based flow control simulation switc hardware traffic patterns

Documents that cite this document

Select link to view other documents in the database that cite this one.

Search Results [PDF FULL-TEXT 860 KB] PREV NEXT DOWNLOAD CITATION


Home | Log-out | Journals | Conference Proceedings | Standards | Search by Author | Basic Search | Advanced Search | Join IEEE | Web Account | New this week | OPAC Linking Information | Your Feedback | Technical Support | Email Alerting | No Robots Please | Release Notes | IEEE Online Publications | Help | FAQ| Terms | Back to Top

Copyright © 2004 IEEE — All rights reserved



> home : > about : > feedback : > login

US Patent & Trademark Office



Search Results

Search Results for: [credit-based flow control] Found 43 of 134,837 searched.

Search within Results

GO > Advanced Search

> Search Help/Tips

Sort by: Title Publication Publication Date Score Binder

Results 1 - 20 of 43 short listing



1 Credit-based flow control for ATM networks: credit update protocol, adaptive credit allocation and statistical multiplexing

95%

H. T. Kung, Trevor Blackwell, Alan Chapman

ACM SIGCOMM Computer Communication Review , Proceedings of the conference on Communications architectures, protocols and applications October 1994 Volume 24 Issue 4

This paper presents three new results concerning credit-based flow control for ATM networks: (1) a simple and robust credit update protocol (CUP) suited for relatively inexpensive hardware/software implementation; (2) automatic adaptation of credit buffer allocation for virtual circuits (VCs) sharing the same buffer pool; (3) use of credit-based flow control to improve the effectiveness of statistical multiplexing in minimizing switch memory. These results have been substantiated by analysi ...

2 Switcherland: a QoS communication architecture for workstation clusters

90%

Hans Eberle , Erwin Oertli

ACM SIGARCH Computer Architecture News, Proceedings of the 25th annual international symposium on Computer architecture April 1998
Volume 26 Issue 3

Computer systems have become powerful enough to process continuous data streams such as video or animated graphics. While processing power and communication bandwidth of today's systems typically are sufficient, quality of service (QoS) guarantees as required for handling such data types cannot be provided by these systems in adequate ways. We present Switcherland, a scalable communication architecture based on crossbar switches that provides QoS guarantees for workstation clusters in the form of ...

3 Reliable and efficient hop-by-hop flow control

85%